

8150/5-V37-306-51-0010-K Art. No. 214174



- Can be used with conventional drives or with variable-frequency drives
- Intelligent design: A single rotary actuator for actuating the main and auxiliary contacts, ≥ 20 ms leading auxiliary contact for safe disconnection
- Designed in accordance with IEC/EN 62626-1, class 1
- The rotary actuator can be locked in the 0-position with three padlocks

MY R. STAHL 8150F



R. STAHL Series 8150/5-V37 safety switches safely disconnect machines and system parts from the energy supply for cleaning and repair as prescribed. All of the installed load disconnect switches have AC-3 switching capacity. The switches can be locked in the 0-position using padlocks.

Technical Data

Explosion Protection

Area of application	European Union (ATEX) IECEx
Application range (zones)	1, 2, 21, 22
IECEx gas certificate	IECEx PTB 09.0049
IECEx gas explosion protection	Ex db eb IIC T6 Gb
IECEx dust certificate	IECEx PTB 09.0049
IECEx dust explosion protection	Ex tb IIIC T80 °C Db
ATEX gas certificate	PTB 09 ATEX 1109
ATEX gas explosion protection	II 2 G Ex db eb IIC T6 Gb
ATEX dust certificate	PTB 09 ATEX 1109
ATEX dust explosion protection	II 2 D Ex tb IIIC T80 °C Db
Certificates	ATEX (PTB), China (NEPSI), IECEx (PTB), India (PESO)
Declaration of conformity	ATEX (EUK), China (CCC)

Electrical Data

Rated operational voltage AC	690 V / 500 V
Rated operational current	63 A (T6) 80 A ()
Rated operational current	63 A
Switching capacity AC-3 230 V	18.5 – 22 kW
Switching capacity AC-3 400 V	30 – 45 kW
Switching capacity AC-3 440 V	37 – 45 kW
Switching capacity AC-3 500 V	37 – 55 kW
Switching capacity AC-3 690 V	55 – -- kW
Auxiliary contact NC	1 NC
Auxiliary contact NO	1 NO/delayed
Frequency range	50 – 60 Hz

Load disconnect switches and motor starters


Safety switch



8150/5-V37-306-51-0010-K Art. No. 214174

Ambient Conditions	
Ambient temperature	-40 °C ... +42 °C -40 °C ... +40 °C
Ambient temperature	-40 °F ... +107 °F -40 °F ... +104 °F
Mechanical Data	
Degree of protection (IP)	IP66
Degree of protection note	according to EN/IEC 60529
Enclosure material	Stainless steel 1.4404, (AISI 316L), brush finished
Solid con. cross-section min.2	35 mm²
Min. fin.str. conn. cr.-sec. 2	35 mm²
Min. solid conn. cr.-sect. AWG	AWG 4
Min. solid con. cr.-sect. AWG2	AWG 2
Min. f.stra. con. cr.-sec. AWG	AWG 4
Min. f.str. con. cr.-sec. AWG2	AWG 2
Connection terminal auxiliary contact min. AWG	AWG 18
Construction type	Standard
Dimension A	360 mm
Dimension A inch	14.17 in
Dimension B	360 mm
Dimension B inch	14.17 in
Dimension C	196 mm
Dimension C inch	7.72 in
Handle colour	Black shroud and handle
Seal	Silicone, foamed
Lockable in	Three times in 0 position
Detailed number of poles	3-pole
Weight	12.6 kg
Weight	27.78 lb
Components	
Entry type	Standard 8161, moulded material
Cable gland	2 x M50 Ø 16 ... 35 mm 1 x M20 Ø 4 ... 13 mm

Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations



Ver- sion	Rated operational current	Product Type	Dimension A [mm]	Dimension B [mm]	Dimension C [mm]
--------------	------------------------------	--------------	---------------------	---------------------	---------------------

Load disconnect switches and motor starters
Safety switch



8150/5-V37-306-51-0010-K Art. No. 214174

3-pole	16 A	8150/5-V37-302-50-....	176.5	176.5	132
	25 A	8150/5-V37-304-50-....	176.5	176.5	132
	40 A	8150/5-V37-305-51-....-K	360	176.5	194
	63 A	8150/5-V37-306-51-....-K	360	360	196
	125 A	8150/5-V37-308-51-....-K	727	360	203

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.