

M63-M20 Art. No. 109374



- Ex e reducers made of glass fibre reinforced polyamide
- Wide selection of metric thread sizes

MY R. STAHL ACC1L



The plastic Ex e reducers make it possible to easily adapt thread sizes. There is a wide selection of different versions available for this. They have global certification according to IECEx and ATEX.

Technical Data

Explosion Protection

Application range (zones)	1, 2, 21, 22
IECEx gas certificate	IECEx PTB 16.0026X
IECEx gas explosion protection	Ex eb IIC Gb
IECEx dust certificate	IECEx PTB 16.0026X
IECEx dust explosion protection	Ex tb IIIC Db
ATEX gas certificate	PTB 04 ATEX 1040 X
ATEX gas explosion protection	Ex II 2 G Ex eb IIC Gb
ATEX dust certificate	PTB 04 ATEX 1040 X
ATEX dust explosion protection	Ex II 2 D Ex tb IIIC Db

Ambient Conditions

Ambient temperature	-40 °C ... +75 °C
---------------------	-------------------

Mechanical Data


Version	Metric/metric
Degree of protection (IP)	IP66
Material	Polyamide, Glass fibre reinforced
Silicone-free	Yes
Design	B
Width across flats	68 mm
Length	22 mm
Outer diameter	75 mm
External thread	M63
Thread size	M63
Thread length	15 mm
Thread pitch	1,5
Thread pitch 2	1,5
Internal thread	M20
Impact strength (IEC 60079)	7 J
Colour	Black

M63-M20 Art. No. 109374

Mechanical Data

Weight	1 g
Weight	0 lb

Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations



Design B
Ga = External thread
Gi = Internal thread
L = Thread length
SW = Width across flats
E = Width across corners
TL = Length

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.