

8174/204-2101-33 Art. No. 139823



- Power supply in Ex d enclosures
- One to 72 cores are combined in one conductor bushing
- Versions: Screwable, pluggable
- For voltages up to max. 1000 V
- For conductor cross-sections up to 70 mm<sup>2</sup>

MY R. STAHL 8174A




The conductor bushings are used to connect the conductors between enclosures with the "flame-proof" and "increased safety" types of protection. The cores are moulded with high-quality, leakage-current-resistant PU resin, meaning that they are insulated from the enclosure wall.

### Technical Data

Explosion Protection	
Application range (zones)	1, 2
IECEX gas certificate	IECEX PTB 06.0081U
IECEX gas explosion protection	Ex db IIC Gb
IECEX firedamp certificate	IECEX PTB 06.0081U
IECEX firedamp protection	Ex db I Mb
ATEX gas certificate	PTB 01 ATEX 1065 U
ATEX gas explosion protection	Ex II 2 G Ex db IIC Gb
ATEX firedamp certificate	PTB 01 ATEX 1065 U
ATEX firedamp protection	Ex I M2 Ex db I Mb
Certificates	ATEX (PTB), China (CQST), IECEX (PTB)
Electrical Data	
Rated operational voltage AC	750 V
Ambient Conditions	
Ambient temperature	-40 °C ... +110 °C
Mechanical Data	
Socket diameter	ø 41
Ex d conductor length	1300 mm
Ex e conductor length	1300 mm
Min. conductor cross section	0.75 mm <sup>2</sup>
Number of core ends	21
Thread size	M48
Thread pitch	1,5
Cable colour	Black
Weight	897 g
Weight	1.98 lb

8174/204-2101-33 Art. No. 139823

### Technical Drawings – Subject to Alterations



## Accessories

### Cheese-head screw



M4 x 6  
Three cheese-head screws are required per stopping plug or threaded piece

**Art. No.**

109806

### Split washer




M4  
Three split washers are required per stopping plug or threaded piece

**Art. No.**

252066

### Stopping plugs




for sealing unused threaded pieces  
Note: Please order cheese-head screws and split washers separately  
Dia. 41 mm, M48 x 1.5

**Art. No.**

139732

### Threaded piece



Note: Please order cheese-head screws and split washers separately  
for pluggable conductor bushings 8174/2  
Drilled hole diameter dia. 41 mm  
Screw-in thread M48 x 1.5

**Art. No.**

140038

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.