Components for system solutions

Residual current Circuit breaker

Circuit breaker

8562/54-4115-250 Art. No. 214958





- · Modular component for residual current monitoring
- Can be used for pulsating direct currents and alternating currents
- · Protection against contact voltages

MY R. STAHL 8562A



The R. STAHL Series 8562 residual current circuit breaker is a component for residual current monitoring and switches systems in the event of residual currents – for the reliable protection of persons in hazardous areas. It is suitable for pulsating direct currents and alternating currents and is designed for rated operational currents of 16, 25 or 40 A and rated residual currents of 10, 30, 100, 300 and 500 mA.

Technical Data

Explosion Protection	
Application range (zones)	1, 2
IECEX gas certificate	IECEx PTB 06.0062U
IECEx gas explosion protection	Ex de IIC T5 Gb
IECEX firedamp certificate	IECEx PTB 06.0062U
IECEx firedamp protection	Ex de I Mb
ATEX gas certificate	PTB 02 ATEX 1049 U
ATEX gas explosion protection	
ATEX firedamp certificate	PTB 02 ATEX 1049 U
ATEX firedamp protection	
FMus certificate	3033692
cFM certificate	3033692C
cCSA certificate	1850696
Electrical Data	
Rated operational current	25 A
Type of voltage	AC
Rated residual current	0.3 A
Auxiliary contacts	Error signal
Auxiliary contacts 2	1 change-over contact
N-pole present	Yes
No. of poles	4
Ambient Conditions	
Ambient temperature	-20 °C 60 °C
Mechanical Data	
Degree of protection (IP)	IP20
Enclosure material	Epoxy resin
Length	156 mm

Components for system solutions



Residual current Circuit breaker Circuit breaker 8562/54-4115-250 Art. No. 214958

Mechanical Data

Length in inches	6.14 in
Mounting depth	97.5 mm
Mounting depth in inches	3.84 in
Weight	1.8 kg
Weight	3.97 lb


Technical Drawings - Subject to Alterations



Fault signal contact 1 change-over contact for error signal (only for types 8562/54-2465-160-4 and 8562/54-2475-4: After the switch trips, the fault message contact can be reset manually)



Dimensional Drawings (All Dimensions in mm [inches]) - Subject to Alterations



Residual current circuit breaker, 4-pole, 8562/54-...

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.