

Load disconnect switches and motor starters

STAHL

Load disconnect switch

63 A / 80 A

8146/5-V11-606-00-0010 Art. No. 221684



- Can be used with conventional drives or with variable-frequency drives
- Intelligent design: A single rotary actuator for actuating the main and auxiliary contacts, ≥ 20 ms leading auxiliary contact for safely disconnecting the frequency converter
- Reliable load disconnect switch with positive opening operation of the main contacts

MY R. STAHL 8146M



R. STAHL Series 8146/5-V11 load disconnect switches can be used as mains connection switches for distributor systems and motor circuits. The standard versions are designed for rated operational currents of up to 80 A – currents of 16 to 630 A are possible. They have AC-3, AC-23 and DC-23 motor switching capacity. They have a large, padlockable rotary actuator in black or red/yellow.

Technical Data

Explosion Protection

Area of application	Canada IECEX USA
Application range (zones)	1, 2, 21, 22
IECEX gas certificate	IECEX PTB 06.0090
IECEX gas certificate	IECEX PTB 06.0090
IECEX gas explosion protection	Ex db eb IIC T6 Gb
IECEX dust certificate	IECEX PTB 06.0090
IECEX dust explosion protection	Ex tb IIIC T80 °C Db
ATEX gas certificate	PTB 01 ATEX 1024
ATEX gas certificate	PTB 01 ATEX 1024
ATEX gas explosion protection	Ex II 2 G Ex db eb IIC T6 Gb
ATEX dust certificate	PTB 01 ATEX 1024
ATEX dust explosion protection	Ex II 2 D Ex tb IIIC T80 °C Db
Certificates	ATEX (PTB), China (NEPSI), IECEX (PTB), India (PESO)
Declaration of conformity	ATEX (EUK), China (CCC)

Electrical Data

Rated operational voltage AC	690 V / 500 V
Rated operational current	63 A / 80 A
Nominal power	60 hp
Auxiliary contact NC	without
Auxiliary contact NO	without
Max. short-circuit protection	125 A
Short-circuit protection, max. 2	160 A
Tripping characteristic	gG
Frequency range	50 – 60 Hz

Load disconnect switches and motor starters

STAHL

Load disconnect switch

63 A / 80 A

8146/5-V11-606-00-0010 Art. No. 221684

Auxiliary Power

Nominal voltage	480 V AC
-----------------	----------

Ambient Conditions

Ambient temperature	-40°C ... +47°C -40°C ... +43°C
---------------------	------------------------------------

Ambient temperature	-40°F ... +116°F -40°F ... +113°F
---------------------	--------------------------------------

Mechanical Data

Degree of protection (IP)	IP66
---------------------------	------

Enclosure material	Polyester, Glass fibre reinforced
--------------------	-----------------------------------

Additional terminal	without
---------------------	---------

Min. connection cross section, solid	25 mm ²
--------------------------------------	--------------------

Solid con. cross-section min.2	35 mm ²
--------------------------------	--------------------

Max. connection cross section, solid	0 mm ²
--------------------------------------	-------------------

Min. connection cross-section, finely stranded	25 mm ²
--	--------------------

Min. fin.str. conn. cr.-sec. 2	35 mm ²
--------------------------------	--------------------

Max. connection cross-section, finely stranded	50 mm ²
--	--------------------

Min. solid conn. cr.-sect. AWG	AWG 4
--------------------------------	-------

Min. solid con. cr.-sect. AWG2	AWG 2
--------------------------------	-------

Max. solid conn. cr.-sect. AWG	AWG 0
--------------------------------	-------

Min. f.stra. con. cr.-sec. AWG	AWG 4
--------------------------------	-------

Min. f.str. con. cr.-sec. AWG2	AWG 2
--------------------------------	-------

Connection terminal auxiliary contact min. AWG	AWG 0
--	-------

Connection terminal auxiliary contact solid max.	AWG 0
--	-------

Connection terminal auxiliary contact finely stranded max.	AWG 0
--	-------

Construction type	Standard
-------------------	----------

Width	340.5 mm
-------	----------

Width, inches	13.41 in
---------------	----------

Height	681.5 mm
--------	----------

Height in inches	26.83 in
------------------	----------

Depth	205 mm
-------	--------

Depth in inches	8.07 in
-----------------	---------

Service life, min.	10 ⁵ operating cycles
--------------------	----------------------------------

Handle colour	Black
---------------	-------

Protective collar colour	Black
--------------------------	-------

Seal	Silicone, foamed
------	------------------

Lockable in	Three times in 0 position
-------------	---------------------------

Detailed number of poles	6-pole
--------------------------	--------

Weight	12.5 kg
--------	---------

Weight	27.5 lb
--------	---------

Components

Entry type	Standard 8161, moulded material
------------	---------------------------------

Load disconnect switches and motor starters



Load disconnect switch


63 A / 80 A

8146/5-V11-606-00-0010 Art. No. 221684

Components


Cable gland	4x M50 Ø 16 to 35 mm 1x M20 Ø 4 ... 13 mm with plug
-------------	--

Technical Drawings – Subject to Alterations



8146/5-V...-6...-00-.010
6-pole

Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations



Version	Rated operational current	Product Type	Dimension A [mm]	Dimension B [mm]	Dimension C [mm]
3-pole	10 A	8146/ 5- V11- 300- 00- 1050 8146/ 5- V11- 300- 00- 0050	112.5	112.5	131
	16 A	8146/ 5- V11- 302- 00- 0050	170	112.5	132
		8146/ 5- V11- 302- 00- 1050	170	112.5	132
		8146/ 5- V11- 302- 00- 1050	170	170	172
		8146/ 5- V11- 102- 00- 0110			
	20 A	8146/ 5- V11- 303- 00- 0010	170	170	132
	25 A	8146/ 5- V11- 104- 00- 0110	227	170	171
		8146/ 5- V11- 304- 00- 1010	170	170	132
	40 A	8146/ 5- V11- 305- 00- 0010- K	340.5	170	176.5
		8146/ 5- V11- 305- 00- 1010- K	340.5	170	176.5
	63–80 A	8146/ 5- V11- 306- 00- 0010- K	340.5	170	195
		8146/ 5- V11- 306- 00- 1010- K	340.5	170	195

Load disconnect switches and motor starters

STAHL

Load disconnect switch

63 A / 80 A

8146/5-V11-606-00-0010 Art. No. 221684

3-pole + N	10 A	8146/ 5- V11- 400- 00- 0050	112.5	112.5	131
	16 A	8146/ 5- V11- 402- 00- 0050 8146/ 5- V11- 402- 00- 1050	170 170	112.5 112.5	132.0 132.0
	20 A	8146/ 5- V11- 403- 00- 0010K	170	170	132
	25 A	8146/ 5- V11- 404- 00- 0010	170	170	132
	40 A	8146/ 5- V11- 405- 00- 0010- K	340.5	340.5	195
	63–80 A	8146/ 5- V11- 406- 00- 0010- K 8146/ 5- V11- 406- 00- 1010- K	340.5 340.5	340.5 340.5	195 195
6-pole	25 A	8146/ 5- V11- 604- 60- 0010	227	170	172

Accessories

Auxiliary contact

Art. No.



Note: The auxiliary contacts can only be retrofitted for 40 A, 63 A and 80 A versions. For all other versions, the auxiliary contact must be ordered separately when placing the order. Retrofitting is not possible for this.

2 NC (8080/1-3)

250 V AC/DC

Max. 6 A

1.5 to 2.5 mm², solid/finely stranded

The switching function of the auxiliary contact depends on the installation slot used.

Left and right: Synchronising

168356

1 NC + 1 NO (8080/1-1)

250 V AC/DC

Max. 6 A

1.5 to 2.5 mm², solid/finely stranded

The switching function of the auxiliary contact depends on the installation slot used.

Left: Delayed (ON), leading (OFF)

Right: Synchronising

168351

2 NO (8080/1-4)

250 V AC/DC

Max. 6 A

1.5 to 2.5 mm², solid/finely stranded

The switching function of the auxiliary contact depends on the installation slot used.

Left and right: Synchronising

168353

Spare Parts

Auxiliary contact key

Art. No.



For removing installed auxiliary contacts

201909

Load disconnect switches and motor starters



Load disconnect switch

63 A / 80 A

8146/5-V11-606-00-0010 Art. No. 221684

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.