

TEF2460162 Art. No. 240988



- Complies with: ICAO Annex 14 Vol. 1 Ch. 6, Low intensity type A or B
- Integrated terminal box with drain plug/breather
- Maintenance free
- Rugged construction
- Encapsulated electronics. No risk of water intrusion to LED's and electronics
- RED+IR Versions are Night Vision Goggle compatible.
- Instant light
- Resistant to vibrations

MY R. STAHL T2460A



Tranberg luminaires are all designed for use in rough environments. It is the policy of Tranberg to provide products and services that meet the highest standards of quality in the industry and the performance needs and expectations of our customers. The design of Tranberg luminaires is based on many years of experience and extensive research in the field of professional Marine lighting. Carefully selected materials are used to ensure maximum performance, low maintenance and a long trouble free life. Applications:

- Obstruction light
- General marking / warning light
- Zone 1, Zone 2 and safe area

Technical Data

Explosion Protection

Area of application	European Union (ATEX) IECEx
Application range (zones)	1, 2
IECEx gas certificate	IECEx Pre 14.0009
IECEx gas explosion protection	Ex e mb op is IIC T5 Gb
ATEX gas certificate	PRESAFE 14 ATEX 4571
ATEX gas explosion protection	Ex II 2 G Ex e mb op is IIC T5 Gb

Electrical Data

Rated operational voltage DC	24 V
Power	10 W

Lighting Data

Lamp	Red LED
Effective luminous intensity	32 cd

Ambient Conditions

Ambient temperature	-55 °C ... +55 °C
Operating temperature	-40 °C ... +55 °C

Mechanical Data


Degree of protection (IP)	IP66
Enclosure material	Brass, Hot-forged
Max. solid connection terminals	4 mm ²
Max. finely stranded connection terminals	2.5 mm ²
Type of connection cable	Finely stranded Solid

TEF2460162 Art. No. 240988

Mechanical Data

Weight	-
Components	
Drilled holes	2 x M25
Cable glands and entries	can be ordered as an accessory
Stopping plugs	Can be ordered as accessories

Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations



Accessories

Cable gland		Art. No.
	M25 Ø 11 ... 15 / 15 ... 20 mm TEF6222502	241042
Dome with gasket		Art. No.
	Dome with gasket	241040
Stopping plug		Art. No.
	M25	241043
	TEF7302101 Breather M25-9 mm, brass	169899
Terminal insert		Art. No.
	Terminal insert	241041

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.