Control device system Series ConSig 8040
Maintained control switch 2-pole with switch element 8008
8040/12E8X-36I08SF05 Art. No. 287030





- Quad certified control stations (NEC®, CE Code, ATEX, IECEx)
- Lightweight enclosure made of fiber glass reinforced polyester (FRP), excellent for corrosive atmospheres
- Offers a variety of pushbuttons, illuminated pushbuttons, control switches and LEDs for different configurations
- Customizable control stations available upon request with different entry, contact options and additional certifications

### MY R. STAHL 8040E



R. STAHL's series 8040 NEC® / CE Code control stations utilize explosion-protected components with non-metallic enclosures for the ultimate flexibility, safety and durability in hazardous and hostile locations. Choose from one of the standard versions or contact us for a customized solution.

#### **Technical Data**

Explosion Protection	
Area of application	European Union (ATEX) Canada IECEx USA
Application range (zones)	1, 2, 21, 22
IECEX gas certificate	IECEx PTB 06.0025
IECEx gas explosion protection	Ex db eb IIC T6 Gb
IECEx dust certificate	PTB 01 ATEX 1105
IECEx dust explosion protection	Ex tb IIIC T80 °C Db
ATEX gas certificate	PTB 01 ATEX 1105
ATEX gas explosion protection	
ATEX dust certificate	PTB 01 ATEX 1105
ATEX dust explosion protection	
Certificate ULus	E182378V1S5
Marking ULus	Class I, Div. 2, Groups A,B,C,D Class II, III, Div. 2, Groups F,G Class I, Zone 1, AEx db eb IIC T6 Enclosure Type 3, 4, 4X
Certificate cUL	E182378V1S5
Marking cUL	Ex db eb IIC T6 Class I, Div. 2, Groups A,B,C,D Class II, III, Div. 2, Groups F,G Enclosure Type 3, 4, 4X
Certificates	ATEX (PTB), Brazil (ULB), Canada (UL), China (NEPSI), IECEx (PTB), India (PESO), Korea (KGS), Taiwan (ITRI), USA (UL)
Ship approval	DNVGL
Notes	Product label for standard configurations as NEC®, CE Code, ATEX, and IECEx. For additional certifications, contact factory.
Electrical Data	
Rated operational voltage AC	690 V



Control device system Series ConSig 8040 Maintained control switch 2-pole with switch element 8008 8040/12E8X-36I08SF05 Art. No. 287030

Electrical Data	
Rated operational current	16 A
Ambient Conditions	
Ambient temperature	-50 °C 40 °C
Ambient temperature °F	-58 °F +104 °F
Mechanical Data	
Degree of protection IP (IEC 60529)	IP66
Enclosure type (UL50 & UL50E)	3, 4, 4X
Enclosure material	Polyester resin, Fiberglass reinforced
Enclosure color	Dark grey
Silicone-free	No
Clamping range AWG	14 AWG
Connection cross-section max.	2.5 mm <sup>2</sup>
Solid connection cross section	0.32 – 2.5 mm <sup>2</sup>
Connection cross-section AWG single stranded	22 AWG 14 AWG
Finely stranded connection cross section	0.32 – 2.5 mm <sup>2</sup>
Finely stranded connection cross-section AWG	22 AWG 14 AWG
Cover fixing type	With captive screws, M4 stainless steel screws
Width	80 mm
Width, inches	3.15 in
Height	139 mm
Height in inches	5.47 in
Depth	72 mm
Depth in inches	2.76 in
Seal	Silicone, foamed
Weight	697 g
Weight	1.54 lb
Mounting / Installation	
Tightening torque of cover screw 1	1.4 N·m
Tightening torque of cover screw 1 lbf in	12.4 lbf in
Components	
Installation position middle	Large handle, LOCAL-REMOTE (1x 90°), With silicone seal
Built-in element middle	Control switch 8008/2-016
Number of poles in built-in element, center position	2
Flange and plates	Metal plate, bottom
Cable glands and entries	NPT 3/4
Entry type	CMP
Entry 1 type	Metal adaptor
Entry 1	NPT 3/4"
Metal entry possible for entry 1	Yes




Control device system Series ConSig 8040
Maintained control switch 2-pole with switch element 8008
8040/12E8X-36I08SF05 Art. No. 287030

#### Technical Drawings - Subject to Alterations



#### Dimensional Drawings (All Dimensions in mm [inches]) - Subject to Alterations



### ConSig 8040/12E

#### **Accessories**

Cylinder lock		Art. No.
	for lockout (bracket Ø 3)	107115
Rotary actuato BG736	r Maxi	Art. No.
	8602C3-736-S-XXX-E08	318418
	Ø 64 mm	
	Handle color: Black	
	Protective collar color: Black	
	Front panel mounting	
	-60 °C 70 °C	
	Silicone-free: No	
	Lockable option (max. 3 times) can be determined using the enclosed closing parts.	
	Lockable handle position: Not defined.	
	In the unmounted assemblies, the standard label is 0/OFF-I/ON and the long coupling part is	
	enclosed.	
	Other labels must be ordered separately.	

### **Spare Parts**

Tag label		Art. No.
	plain for attaching to enclosure 8040; moulded material; with paper insert strip	130673



Control device system Series ConSig 8040
Maintained control switch 2-pole with switch element 8008
8040/12E8X-36I08SF05 Art. No. 287030

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.